

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-246780

(43)Date of publication of application : 12.09.2000

(51)Int. CI.

B29C 47/12
// C03C 27/06

(21)Application number : 11-050790

(71)Applicant : ASAHI GLASS CO LTD

(22)Date of filing : 26.02.1999


(72)Inventor : OKINO NAOKI
ONABEDA YUICHI
ITO MASAO

(54) RESIN EXTRUDER, AND RESIN EXTRUSION-MOLDING

(57)Abstract:

PROBLEM TO BE SOLVED: To stably change the extrusion amount of a resin material, and easily recover the excessive resin material.

SOLUTION: To a location being adjacent to the discharging port 16 of an extruder 13, a switching block 25 having a built-in switching valve 24 which can be switched to a resin feeding port 22 and a resin discharging port 23, is connect-arranged, and to the resin feeding port 22 of the switching block 25, a die 31 equipped with a flow rate regulating valve 33 communicating with a nozzle opening 32, is connected with a resin feeding pipe 30.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision
of rejection][Kind of final disposal of application
other than the examiner's decision of
rejection or application converted
registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

✓ [Number of appeal against examiner's
decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office

BEST AVAILABLE COPY